



Shenzhen Absen Optoelectronic Co., Ltd.

JD3.9-HA - Specifications

Version : V20210312

Parameter		Value
Physical Parameter	LED Type	SMD 3in1 1515
	Pixel Pitch (mm)	3.9(H)/7.8(V)
	Panel Dimensions (WxHxD)/(mm)	1000x500x90
	Pixel Per Panel	256x64
	Panel Weight (kg)	5
	Panel Material	Die Casting Aluminum
	Module Dimensions (WxH)/(mm)	500x250
	Transparency	80%
Optoelectronic Parameter	Brightness (nit)	5500
	Refresh Rate (Hz)	3840
	Gray scale (Bit)	14
	Contrast Ratio	/
	Color Temperature (K)	6500
	Viewing Angle (H/V) (°)	160/160
	Driving Type	1/4
	AC Operating Voltage (V)	100 ~ 240
	Power Consumption (Max./Avg.)(W/m ²)	675/225
Application Parameter	Storage Temperature (°C)	-40 ~ +60
	Operating Temperature (°C)	-10 ~ +40
	Storage Humidity (RH)	10% ~ 85%
	Operating Humidity (RH)	10% ~ 80%
	IP Rating (Front/Rear)	IP30
	Module Maintenance	Front or Rear
	PSU & Others Maintenance	Front or Rear
	Panel Installation Type	Hanging/Stacking
	Max Rigging QTY.	/
	Certificate	CCC,CE,ETL,FCC

Remark:Power consumption tolerance: ±15%, according to the actual situation.