

K2.5 PLUS - Specifications

Version : V2021/10/16

Parameter		Value
Physical Parameter	LED Type	Black SMD 3in1
	Pixel Pitch (mm)	2.50
	Panel Dimensions (WxHxD)/(mm)	500×750×62
	Pixel Per Panel	200×300
	Panel Weight (kg)	8.5
	Panel Material	Die Casting Aluminum
	Module Dimensions (WxH)/(mm)	250×250
Physical Parameter	Brightness (nit)	700
	Refresh Rate (Hz)	1920/3840
	Gray scale(Bit)	12 Bit/13 Bit
	Contrast Ratio	5000:1
	Color Temperature (K)	6500
	Viewing Angle (H/V) (°)	160/160
	Driving Type	1/50
	AC Operating Voltage (V)	100 ~ 240 V
	Power Consumption (Max./Avg.)(W/m ²)	450/150
Physical Parameter	Storage Temperature (°C)	-40 ~ +60
	Operating Temperature (°C)	-10 ~ +40
	Storage Humidity (RH)	10% ~ 85%
	Operating Humidity (RH)	10% ~ 80%
	IP Rating (Front/Rear)	IP40/IP21
	Module Maintenance	Front or Rear
	PSU & Others Maintenance	Front or Rear
	Panel Installation Type	Hanging/Stacking/Wall Mounting
	Max Rigging QTY.	8
	Certificate	CCC,CE,ETL,ROHS,FCC

Remark:Power consumption tolerance: ±15%, according to the actual situation.